

REPORT DOCUMENTATION PAGE

Form Approved
OMB No. 0704-0188

Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing this collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden to Department of Defense, Washington Headquarters Services, Directorate for Information Operations and Reports (0704-0188), 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to any penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number. PLEASE DO NOT RETURN YOUR FORM TO THE ABOVE ADDRESS.

1. REPORT DATE (DD-MM-YYYY)		2. REPORT TYPE Technical Papers		3. DATES COVERED (From - To)	
<div style="border: 1px solid black; border-radius: 50%; padding: 20px; text-align: center; font-size: 2em;"> Please see attached </div>				4. TITLE AND SUBTITLE	
				5a. CONTRACT NUMBER	
				5b. GRANT NUMBER	
				5c. PROGRAM ELEMENT NUMBER	
<div style="border: 1px solid black; border-radius: 50%; padding: 20px; text-align: center; font-size: 2em;"> Please see attached </div>				6. AUTHOR(S)	
				5d. PROJECT NUMBER 2302	
				5e. TASK NUMBER M162	
				5f. WORK UNIT NUMBER 346120	
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) Air Force Research Laboratory (AFMC) AFRL/PRS 5 Pollux Drive Edwards AFB CA 93524-7048				8. PERFORMING ORGANIZATION REPORT	
9. SPONSORING / MONITORING AGENCY NAME(S) AND ADDRESS(ES) Air Force Research Laboratory (AFMC) AFRL/PRS 5 Pollux Drive Edwards AFB CA 93524-7048				10. SPONSOR/MONITOR'S ACRONYM(S)	
				11. SPONSOR/MONITOR'S NUMBER(S) Please see attached	
12. DISTRIBUTION / AVAILABILITY STATEMENT Approved for public release; distribution unlimited.					
13. SUPPLEMENTARY NOTES					
14. ABSTRACT					
15. SUBJECT TERMS					
16. SECURITY CLASSIFICATION OF:			17. LIMITATION OF ABSTRACT	18. NUMBER OF PAGES	19a. NAME OF RESPONSIBLE PERSON
a. REPORT	b. ABSTRACT	c. THIS PAGE	<div style="border: 1px solid black; border-radius: 50%; padding: 10px; text-align: center; font-size: 1.5em;"> A </div>		Leilani Richardson
Unclassified	Unclassified	Unclassified			19b. TELEPHONE NUMBER (include area code) (661) 275-5015

20030129 199

MEMORANDUM FOR PRS (In-House Publication)

FROM: PROI (STINFO)

11 March 2002

SUBJECT: Authorization for Release of Technical Information, Control Number: **AFRL-PR-ED-AB-2002-051**
C.T. Liu (PRSM) & Fu-Pen Chiang (UNY), "Investigating the Deformation and Failure Mechanisms in
Bi-Material Systems under Tension"

14th U.S. National Congress Theoretical & Applied Mechanics
(Blacksburg, VA, 23-28 June 2002) (Deadline: 12 April 2002)

(Statement A)

1. This request has been reviewed by the Foreign Disclosure Office for: a.) appropriateness of distribution statement, b.) military/national critical technology, c.) export controls or distribution restrictions, d.) appropriateness for release to a foreign nation, and e.) technical sensitivity and/or economic sensitivity.

Comments: _____

Signature _____ Date _____

2. This request has been reviewed by the Public Affairs Office for: a.) appropriateness for public release and/or b) possible higher headquarters review.

Comments: _____

Signature _____ Date _____

3. This request has been reviewed by the STINFO for: a.) changes if approved as amended, b.) appropriateness of references, if applicable; and c.) format and completion of meeting clearance form if required

Comments: _____

Signature _____ Date _____

4. This request has been reviewed by PR for: a.) technical accuracy, b.) appropriateness for audience, c.) appropriateness of distribution statement, d.) technical sensitivity and economic sensitivity, e.) military/national critical technology, and f.) data rights and patentability

Comments: _____

APPROVED/APPROVED AS AMENDED/DISAPPROVED

PHILIP A. KESSEL

Date

Technical Advisor

Space and Missile Propulsion Division

Investigating the Deformation and Failure Mechanisms in Bi-Material Systems under
Tension
C.T. Liu
AFRL/PRSM 10 E. Saturn Blvd.
Edwards AFB CA 93524-7680

Fu-Pen Chiang
Department of Mechanical Engineering
State University of New York
Stony Brook, N. Y. 11790

Bonded sandwich laminates are being used widely in various industries. They have been successfully used in aircraft and space structures, pipes, chemical tanks, ship hulls, and in other structural applications in which a high strength-to-weight ratio is a desirable feature.

Joining structural components with adhesives provides a number of advantages. Bonding does not require rivet holes, which are stress raisers and may cause premature failure either under static or fatigue loading. In fact, it has been shown that the fatigue strength of a stiffened panel in an aircraft structure is considerably improved when the stiffeners are bonded to the panel. The bonding of damping materials to metal sheets, to form a sandwich structure, currently is being considered as an effective way to control noise-induced fatigue (sonic fatigue) of airframes. In solid rocket motor design, the bonding of insulation materials to motor casings is used to protect the casing from high temperature after the motor is fired.

It is well known that there are imperfections existing in bonded systems. These imperfections may be produced during the fabrication process of the systems. In analyzing the strength of the bonded system, the localized imperfection may be idealized as a crack in the material. In addition to the imperfections, cracks also can be developed in the material by service loads during the life of the structures. In determining the residual strength or the remaining service life of a bonded structure with cracks, the constitutive behavior of the bonded systems needs to be determined.

In this study, the strain distributions and the constitutive relations in a bonded bi-material specimen under a constant displacement rate of 0.0254 cm./min. were determined using computer aided speckle interferometry techniques. Two different viscoelastic materials were used to make sandwiched specimens. The two outer layers of the specimen are made of a particle-reinforced rubber, whereas the middle layer is a non-reinforced rubber. The heights of the outer layer and the middle layer are 5.08 cm. and 0.254 cm., respectively. The thickness of the specimen is 0.508 cm. and the width of the specimen varies from 0.508 cm. to 2.58 cm. The experimental data were analyzed and the effects of specimen geometry on strain distributions and failure mode in the specimen were discussed.